

1200
WZ



G-LITES™

New era of Lighting

1200 WZ

LAMP

QMax (included):
QT11200 SA/DE (6000K)
Phillips:
MSR 1200 SA/2 DE (6000K).
Average lamp life:
Phillips: 800+ hours
QMax: 750 hours

COLOR

8 main interchangeable colors (7 + 1 white/open). Can freely move clockwise or anticlockwise, fast or slow.
CMY CTO color mixing. Adjustable color change rate (auto adjusting different collors).

EFFECTS

12° - 17° stepless zooming freely tunable.

DIMMER-SHUTTER-STROBE

0 - 100% mechanical linear dimming (adjustable from full blanking to full opening effects).
1-7 flashes/second ultra high speed strobe effect.

PAN TILT

Horizontal direction 540° scanning, smooth scanning action and accurate orientation.
Vertical 250° scanning, smooth scanning action and accurate orientation.
Pan/Tilt lock
Pan/Tilt w 8/16 bit resolution.
Automatic Pan/Tilt repositioning.
Precise adjustment on horizontal and vertical position.
Precise speed adjustment on horizontal and vertical position.

INPUT

3 pin or 5 pin in and out DMX 512 signal.
16 channel (16 bit) or 12 channel (8 bit).

SET UP

Separate motor debug remote control.
Separate DMX address functions remote control: stand, inverted, light on, light off.
Auto test all functions.
Display "flip" function 180° rotation.
Working temperature adjustment.

POWER

Magnetic Ballast Version.
200-220 V - 60 Hz.
100-120 V - 60 Hz (optional).
220-240 V - 50 Hz (optional).
Built-in over heat protection and high voltage protection.
PCF power factor compensation.
According to various kinds of safety standards, IP20 protect grades, the cable accords to CE20/22 standard.

CONSUMPTION

Power consumption: 1400W.

DIMENSIONS

L21xW18xH44 inches.
L534xW445xH1118 mm.

NET WEIGHT

49 Kg. / 107 Lb.

GROSS WEIGHT

78 Kg. / 173 Lb.



Grace Lites Corporation

42245 Remington Ave. Suite B16
Temecula, California, 92590
Customer Service Phone Number: 951 695 8615
Fax Line: 951 695 8600 or 775 242 8712

Website: www.g-lites.com
E-mail: info@g-lites.com