

1500
SZ



G•LITES™

New era of Lighting

1500 SZ

LAMP

Osram (included)
HTI 1500 W/D7/60 (6000 K)
Average Lamp life – 800+ hours (OSRAM Lamp)

COLOR

8 main colors, with fast one-way rolling effect
CMY + CTO color mixing system
Color mixing CMY + CTO independently variable from 0 – 100%

GOBO

9 metal and glass gobos (5 glass and 4 metal).
9 gobos adopt two groups of gobo wheel design.
All gobos adopt the plug pull frame, and they can be changed very easy by opening their springs.
Rotating gobos can spin bidirectional and rotation speed is adjustable (fast/slow), indexing, continuous gobo rotation and shake.
Rotating gobo's angle can be separately adjusted (ensure the consistent of the gobo's direction and angle).

OPTICS

Motorized zoom and focus
Motorized iris (adjustable aperture size)
Zoom: 8° - 28°
Infinite magnifying focus function

DIMMER-SHUTTER-STROBE

0 – 100% mechanical linear dimming (adjustable from full blanking to full opening effects).
1-7 flashes/second ultra high speed strobe effect.

PAN TILT

Horizontal direction 540° scanning, smooth scanning action and accurate orientation.
Vertical 250° scanning, smooth scanning action and accurate orientation.
Pan/Tilt lock.
Automatic Pan/Tilt repositioning.
Precise adjustment on horizontal and vertical position.
Precise speed adjustment on horizontal and vertical position.

INPUT

3 pin or 5 pin in and out.
Signal: DMX 512
Channel: 28

SET UP

Built-in rechargeable battery, this function allows set functions on the fixture without being linked to any power source (addressing, lamp time, etc).
Remote lamp strike ON/OFF.
Remote motor debug/reset.
Separate motor debug remote control.
Separate DMX address for remote control: stand, inverted, light on/light off.
Auto test for all functions.
Display "flip" function 180° rotation.

POWER

Electronic Ballast Version
198 V – 240 V – 50/60 Hz
Intelligent tracking and power-economized system technique which can reduce the bulb's power timely. When the shutter is closed, the power of the bulb will be reduce in 50% without affecting the normal performance of the lamp.

CONSUMPTION

Power Consumption: 1800 W.

INSTALLATION

Quarter turn lock system.

DIMENSION

L515 W406 H851 mm / L20 W16 H34 in
With flightcase:
L580 W472 H1052 mm / L23 W19 H41 in

WEIGHT

Net Weight: 47 kg / 104 lb
Gross Weight: 74.5 kg. / 164 lb



Grace Lites Corporation

42245 Remington Ave. Suite B16
Temecula, California, 92590
Customer Service Phone Number: 951 695 8615
Fax Line: 951 695 8600 or 775 242 8712

Website: www.g-lites.com
E-mail: info@g-lites.com