

600
WZ



G•LITES™

New era of Lighting

600
WZ

LAMP

QMax (included):
QSI575HR (6000K)
Phillips:
MSI 575 (5600K).
Average lamp life:
Phillips: 750+ hours
QMax: 1000 hours

COLOR

8 main interchangeable colors (7 + 1 white/
open). Can freely move clockwise or
anticlockwise, fast or slow.
CMY CTO color mixing. Adjustable color change
rate (auto adjusting different colors).

EFFECTS

12° - 17° stepless zooming feature, freely tunable.

DIMMER-SHUTTER-STROBE

0 – 100% mechanical linear dimming (adjustable
from full blanking to full opening effects).
1-7 flashes/second ultra high speed strobe effect.

PAN TILT

Horizontal direction 540° scanning, smooth
scanning action and accurate orientation.
Vertical 250° scanning, smooth scanning action
and accurate orientation.
Pan/Tilt lock
Pan/Tilt w 8/16 bit resolution.
Automatic Pan/Tilt repositioning.
Precise adjustment on horizontal and vertical
position.
Precise speed adjustment on horizontal and
vertical position.

INPUT

3 pin or 5 pin in and out DMX 512 signal.
16 channel (16 bit) or 12 channel (8 bit).

SET UP

Separate motor debug remote control.
Separate DMX address functions remote control:
stand, inverted, light on, light off.
Auto test all functions.
Display “flip” function 180° rotation.
Working temperature adjustment.

POWER

Magnetic Ballast Version.
200-220 V – 60 Hz.
100-120 V – 60 Hz (optional).
220-240 V – 50 Hz (optional).
Built-in over heat protection and high voltage
protection.
PCF power factor compensation.
According to various kinds of safety standards,
IP20 protect grades, the cable accords to
CE20/22 standard.

CONSUMPTION

Power consumption: 680W.

DIMENSIONS

L21xW18xH44 inches.
L534xW445xH1118 mm.

NET WEIGHT

46 Kg. / 102 Lb.

GROSS WEIGHT

77 Kg. / 169 Lb.



Grace Lites Corporation
42245 Remington Ave. Suite B16
Temecula, California, 92590
Customer Service Phone Number: 951 695 8615
Fax Line: 951 695 8600 or 775 242 8712

Website: www.g-lites.com
E-mail: info@g-lites.com